

Product Data Sheet

Description

Ultratherm tile adhesive is a water based acrylic adhesive for bonding Ultratherm tiles to plastered walls.

Technical Data

Chemical Base	Acrylic
Viscosity	Thixotropic paste
Specific Gravity	1.20 – 1.30 at 20°C
Solids	68 – 75% at 20°C
Service Temperature	-20°C – +100 °C
Colour	Beige
Chemical Resistance	Resistant to water, dilute acids, alkalis and aliphatic oils
Storage Temperature	10°C to 25°C. Lower temperatures can cause permanent damage to product
Shelf Life	6 months in unopened container
Packaging	10kg poly bucket
Cleaning Solvent	Water
Coverage (per side)	Approximately 1m ² per kg using a 3mm notched towel
Application Temperature	10°C to 30°C
Substrate Preparation	All surfaces should be free of contamination by dust, grease, oils or release agents.

Please Consult the Ultratherm adhesive Health & Safety Data Sheet for statutory regulation information.

Information relating to Ultratherm tile adhesive is based on tests carried out by the manufacturer under laboratory conditions. If Ultratherm tile adhesive is not used in accordance with our instructions or are used under conditions which vary from our laboratory, they may not perform in accordance with any information provided and we shall not have any liability in this case.

Issue Date – 12th May 2026

Ultratherm
Birdsgrove SK17 0DH
0800 1691106